

KIMEX PET S.A. DE C.V.

KM. 26.5 AUTOPISTA MEXICO-QUERETARO
APARTADO POSTAL No. 168 TLALNEPANTLA,
ESTADO DE MEXICO, C.P. 54020 MEXICO
TELS: 53.66.90.00



## PET PREFORM SPECIFICATIONS SHEET

DATE: Feb 12 th, 16

REFERENCE: PRE-KX-01

MADE BY: PET LABORATORY

REV: "O"

## TECHNICAL SHEET: 17 PCO 1816 PREFORM


PREFORM: 17		FINISH: PCO 1816	COLO	DR: WITHOUT COLOR, PIGMENTED, CLE OR OPAQUE	AR,		
COMPOSITION:	PET RESIN (POLYETHYLENE TEREPHTHALATE) WITH OR WITHOUT PIGMENT						
INTENDED USE:	MANUFACTURE OF PACKAGING						
PACKING:	GAYLORD CONTA POLYETHYLENE IN	NER (CARTON BULK BOX), STRAPPED / NER LINER.	AND LABELED,	PIECES PER BOX: 1	5,216		
STORAGE:		HE BOX TO MOISTURE, UV RAYS, AVOI ACE, WITHOUT DUST.	D BRUSH MOVEME	INTS			

QUALITY LABORATORY TESTS:

WEIGHT, DIMENSIONAL ANALYSIS, ACETALDEHYDE AND INTRINSEC VISCOSITY.

## DIMENSIONS:

No.	CHARACTERISTIC		SPECIFICATIONS	
INO.	CHARACIERISTIC	UNITS	MIN	MAX
1	WEIGHT	g	16.90	17.50
2	CONTROL DIAMETER AT TOP OF FINISH	mm	21.61	21.87
3	THREAD ROOT DIAMETER	mm	24.36	24.66
4	THREAD CREST DIAMETER	mm	27.30	27.56
5	TAMPER EVIDENT BEAD DIAMETER	mm	27.84	28.10
6	SUPPORT LEDGE DIAMETER	mm	32.62	33.38
7	HEIGHT FROM SUPPORT LEDGE	mm	21.00	21.40
8	THICKNESS 1	mm	2.16	2.42
9	THICKNESS 2	mm	2.16	2.42
10	THICKNESS 3	mm	2.16	2.42
11	THICKNESS 4	mm	2.16	2.42
12	TOTAL PREFORM HEIGHT	mm	86.10	86.50



NOTE: THICKNESS 1, 2, 3 AND 4 ARE  $90^{\circ}$  EACH OTHER. HEIGHT FROM SUPPORT LEDGE = HEIGHT OF FINISH

HTPP-01