

KIMEX PET S.A. DE C.V.

KM. 26.5 AUTOPISTA MEXICO-QUERETARO
APARTADO POSTAL No. 168 TLALNEPANTLA,
ESTADO DE MEXICO, C.P. 54020 MEXICO
TEL S. 53.65.09.00



## PET PREFORM SPECIFICATIONS SHEET

DATE: Feb 12 th, 16

REFERENCE: PRE-KX-01

MADE BY: PET LABORATORY

REV: "O"

## TECHNICAL SHEET: 25/1 PCO 1816 PREFORM


PREFORM: 25/1		FINISH: PCO 1816 COLOR:		WITHOUT COLOR, PIGMENTED, CLEAR, OR OPAQUE				
COMPOSITION:	PET RESIN (POLYE	OLYETHYLENE TEREPHTHALATE) WITH OR WITHOUT PIGMENT						
INTENDED USE:	MANUFACTURE OF PACKAGING							
PACKING:	GAYLORD CONTA POLYETHYLENE IN	AINER (CARTON BULK BOX), STRAPPED AND LABELED, INNER LINER.				PIECES PER BOX:	13,008	
STORAGE:		HE BOX TO MOISTURE, UV RAYS, AVC ACE, WITHOUT DUST.	OID BRUSH MO	VEMENTS	5			

QUALITY LABORATORY TESTS:

WEIGHT, DIMENSIONAL ANALYSIS, ACETALDEHYDE AND INTRINSEC VISCOSITY.

## DIMENSIONS:

No.	CHARACTERISTIC		SPECIFICATIONS	
INO.	CHARACIERISTIC	UNITS	MIN	MAX
1	WEIGHT	g	24.47	25.07
2	CONTROL DIAMETER AT TOP OF FINISH	mm	21.71	21.97
3	THREAD ROOT DIAMETER	mm	24.36	24.66
4	THREAD CREST DIAMETER	mm	27.30	27.56
5	TAMPER EVIDENT BEAD DIAMETER	mm	27.84	28.10
6	SUPPORT LEDGE DIAMETER	mm	32.62	33.38
7	HEIGHT FROM SUPPORT LEDGE	mm	21.00	21.40
8	THICKNESS 1	mm	3.22	3.48
9	THICKNESS 2	mm	3.22	3.48
10	THICKNESS 3	mm	3.22	3.48
11	THICKNESS 4	mm	3.22	3.48
12	TOTAL PREFORM HEIGHT	mm	100.30	100.70



NOTE: THICKNESS 1, 2, 3 AND 4 ARE 90° EACH OTHER.  $\label{eq:HEIGHT FROM SUPPORT LEDGE} = \text{HEIGHT OF FINISH}$ 

HTPP-01