

KIMEX PET S.A. DE C.V.

KM. 26.5 AUTOPISTA MEXICO-QUERETARO
APARTADO POSTAL No. 168 TLALNEPANTLA,
ESTADO DE MEXICO, C.P. 54020 MEXICO
TEL S. 53.65.09.00



PET PREFORM SPECIFICATIONS SHEET

DATE: Feb 12 th, 16

REFERENCE: PRE-KX-01

MADE BY: PET LABORATORY

REV: "O"

TECHNICAL SHEET: 56 PCO 1816 PREFORM


PREFORM: 56		FINISH: PCO 1816		COLOR:	WITHOUT COLOR, PIGMENTED, CLEAR, OR OPAQUE			
COMPOSITION:	PET RESIN (POLYE	PET RESIN (POLYETHYLENE TEREPHTHALATE) WITH OR WITHOUT PIGMENT						
INTENDED USE:	MANUFACTURE OF PACKAGING							
PACKING:	GAYLORD CONTA POLYETHYLENE IN	INER (CARTON BULK BOX), STRAPPED AND LABELED, INER LINER.				PER BOX:	5,808	
STORAGE:		HE BOX TO MOISTURE, UV RA	AYS, AVOID BRUSH MC	VEMENTS				

QUALITY LABORATORY TESTS:

WEIGHT, DIMENSIONAL ANALYSIS, ACETALDEHYDE AND INTRINSEC VISCOSITY.

DIMENSIONS:

No.	CHARACTERISTIC		SPECIFICATIONS	
NO.	CHARACTERISTIC	UNITS	MIN	MAX
1	WEIGHT	g	55.50	56.10
2	CONTROL DIAMETER AT TOP OF FINISH	mm	21.61	21.87
3	THREAD ROOT DIAMETER	mm	24.36	24.66
4	THREAD CREST DIAMETER	mm	27.30	27.56
5	TAMPER EVIDENT BEAD DIAMETER	mm	27.84	28.10
6	SUPPORT LEDGE DIAMETER	mm	32.62	33.38
7	HEIGHT FROM SUPPORT LEDGE	mm	21.00	21.40
8	THICKNESS 1	mm	3.98	4.24
9	THICKNESS 2	mm	3.98	4.24
10	THICKNESS 3	mm	3.98	4.24
11	THICKNESS 4	mm	3.98	4.24
12	TOTAL PREFORM HEIGHT	mm	151.54	153.06



NOTE: THICKNESS 1, 2, 3 AND 4 ARE 90° EACH OTHER. HEIGHT FROM SUPPORT LEDGE = HEIGHT OF FINISH

HTPP-01